



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
17.04.2002 Bulletin 2002/16

(51) Int Cl.7: **H01M 10/40, H01M 2/16,**
H01M 4/62

(21) Application number: **01308657.4**

(22) Date of filing: **10.10.2001**

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR
 Designated Extension States:
AL LT LV MK RO SI

(72) Inventors:
 • **Morigaki, Kenichi**
Nishinomiya-shi, Hyogo 663-8024 (JP)
 • **Nanai, Norishige**
Hirakata-shi, Osaka 573-0036 (JP)
 • **Shibano, Yasuyuki**
Sakai-shi, Osaka 599-8273 (JP)

(30) Priority: **11.10.2000 JP 2000310764**

(71) Applicant: **MATSUSHITA ELECTRIC INDUSTRIAL**
CO., LTD.
Kadoma-shi, Osaka 571-8501 (JP)

(74) Representative: **Nachshen, Neil Jacob et al**
D Young & Co
21 New Fetter Lane
London EC4A 1DA (GB)

(54) **Lithium polymer battery and method for producing the same**

(57) In order to improve a storage stability at high temperatures of a lithium polymer battery including: a positive electrode (4) comprising a lithium-containing complex oxide; a negative electrode (6) comprising a material capable of absorbing and desorbing a lithium ion; and a separator (5) comprising a liquid organic electrolyte and a host polymer retaining the liquid organic electrolyte, the separator is rendered homogeneous and excellent in the affinity with the organic electrolyte by using a crosslinked copolymer having a main-chain comprising a vinylidene fluoride unit and a side-chain comprising an alkylene oxide unit and at least one of an acrylate unit and methacrylate unit as the host polymer.

FIG. 1

